

小一体机更换最新版本web中间件

1.首先先将原来工作的web中间件卸载。

```
root@raspberrypi:/jdsms/JDSmsService-web366# ls
accounts  conf      Doc       install   JDSmsService-web  logs      Readme.txt  restart-jdsms.sh
bin       console  getSystemKind.sh  jdk       language          mysql     reAppServiceRed.sh  temp
CHANGELOG derby.log  infos      JDSmsMySQL  lib              nohup.out  reAppService.sh  uninstall
root@raspberrypi:/jdsms/JDSmsService-web366# ./uninstall
Stopping JDSmsService-web366 ... (pid=1222) [OK]
=====
warn: JDSmsService-web366 is not running
=====
./uninstall: line 2: /etc/init.d/JDSmsMySQL: No such file or directory
root@raspberrypi:/jdsms/JDSmsService-web366#
```

2.将旧版本web中间件目录备份一下。

```
./uninstall: line 2: /etc/init.d/JDSmsMySQL: No such file or directory
root@raspberrypi:/jdsms/JDSmsService-web366# cd ..
root@raspberrypi:/jdsms# mkdir /bak
root@raspberrypi:/jdsms# /bak
-bash: /bak: Is a directory
root@raspberrypi:/jdsms# mv * /bak
root@raspberrypi:/jdsms# ls
root@raspberrypi:/jdsms# ls /bak/
JDSmsService-web366  JDSmsService-web366-smallpc-withdbpool-20180502.tar.gz
root@raspberrypi:/jdsms#
```

3.将新版本web中间件上传到小一体机然后进行解压安装。

```
root@raspberrypi:/jdsms# ls
JDSmsService-web367-linux-x86-2019.05.29.tar.gz
root@raspberrypi:/jdsms# tar zxf JDSmsService-web367-linux-x86-2019.05.29.tar.gz
root@raspberrypi:/jdsms# ls
JDSmsService-web367  JDSmsService-web367-linux-x86-2019.05.29.tar.gz
root@raspberrypi:/jdsms#
```

4.修改新小一体机配置文件Conf\JDSMSServer.conf

```
root@raspberrypi:/jdsms# cd JDSmsService-web367/
root@raspberrypi:/jdsms/JDSmsService-web367# vim conf/JDSMSServer.conf
```

#settings.machine_model=LINUX (pc端web中间件需放开)

settings.machine_model=AIO (小一体机需要放开)

```
settings.timeframe.low=0900-2200
settings.timeframe.normal=0000-2359
settings.timeframe.high=0000-2359
settings.retries_time=300000
settings.phone_msg_max_count=0
settings.settlement_interval_day_begin=15
settings.settlement_interval_hour_begin=0
settings.settlement_interval_min_begin=0
settings.settlement_interval_second_begin=0
settings.settlement_interval_day_end=14
settings.settlement_interval_hour_end=23
settings.settlement_interval_min_end=59
settings.settlement_interval_second_end=59
settings.push_messages_interval=3600
```

```
#settings.machine_model=LINUX
settings.machine_model=AIO
```

```
#web console
console.username=admin
console.password=admin
console.port=8090
service.ip=119.90.56.86
settings.device_using = yes
settings.phone_using = no
settings.gateway_using = no
settings.using_sorted = 1
settings.system_suffix =
settings.push_fail_interval = 14
-- INSERT --
```

5.将新版本jdk目录mv到其它目录，将旧版本jdk目录mv到新版本根目录下。

```
root@raspberrypi:/jdsms/JDSmsService-web367# ls
accounts  console      infos        JDSmsService-web  logs        reAppServiceRed.sh  uninstall
bin       derby.log   install     language          mysql       reAppService.sh
CHANGELOG Doc          jdk         lib               nohup.out   restart-jdsms.sh
conf     getSystemKind.sh JDSmsMySQL logon.jsp        Readme.txt  temp
root@raspberrypi:/jdsms/JDSmsService-web367# mv jdk /b
bak/ bin/ boot/
root@raspberrypi:/jdsms/JDSmsService-web367# mv jdk /bak/
root@raspberrypi:/jdsms/JDSmsService-web367# mv /bak/
jdk/
JDSmsService-web366/
JDSmsService-web366/
root@raspberrypi:/jdsms/JDSmsService-web367# mv /bak/JDSmsService-web366/jdk .
root@raspberrypi:/jdsms/JDSmsService-web367#
```

6.启动web中间件 登录web中间件查看是否为最新版本。

```
root@raspberrypi:/jdsms/JDSmsService-web367# mv /bak/JDSmsService-web366/jdk .
root@raspberrypi:/jdsms/JDSmsService-web367# ./install
[....] Starting JDSmsMySQL (via systemctl): JDSmsMySQL.serviceFailed to start JDSmsMySQL.service: Unit JDSmsMySQL.service fa
iled to load: No such file or directory.
failed!
Starting JDSmsService-web366 ... (pid=1958) [OK]
root@raspberrypi:/jdsms/JDSmsService-web367#
```

- 管理菜单
- 首页
- 设备配置
- 手机设备
- 数据源设置
- 公共地址本
- 地址本
- 发送短信
- 待发送列表
- 短信记录
- 系统日志
- 系统设置
- 网关服务
- 系统管理
- 修改密码
- 退出控制台

您好, admin! 欢迎您使用金笛短信中间件web版。



Copyright © 2019 金笛软件
Release:20190529
当前用户:admin